


## ・スリップリング

(Slip Ring)



### 略号/SYMBOL

<構造: Classification of structure>

- ・M(モールド) : Molding
- ・SF(焼きバメ) : Shrinkage fitting

<金属材料: metal material>

- ・Cu : Copper material
- ・Bs : Brass material
- ・SUS: Stainless steel material

## S R 寸 法 表

No.1

### ●スリップリング Slip rings

P	D1	L1	L2	d	備考
1	20	14.5	10	5.2	M-Cu
	34	12	9	16	M-Cu,BS
	40	10	8	15	M-Cu
	48	11	9	20.5	M-Cu
	48	14	9	20.5	M-Cu
	50.8	19	15	22	M-Cu
2	20	22	9	8	M-Cu
	32	25	9.5	16	M-BS
	33	24.7	10	17.3;18.3	M-SUS
	35	22	8	17	M-Cu
	38	23	7.5	20	M-Cu
	38	30	9	19	M-BS
	40	39	10	15	M-SUS
	43	25.2	10	20.4;25.4	M-SUS
	45	25	7.5	23	M-BS
	48	28	9	20.5	M-Cu
	48	41	11	28	M-Cu
	50	40.5	10	28	M-Cu
	50.8	24	9.5	34.5	M-Cu
	52	32	10	28	M-SUS,BS
	60	34	10	33	M-SUS
	63	30	10	26	M-BS
	63	48	10	33	M-SUS
	87	44	13	47	M-SUS
89	44	13	28	SF-SUS	
134	44	13	57~64	SF-SUS	
184	66	22	87	SF-Cu	
220	68	20	107~137	SF-SUS	
3	38	70.5	7	10	M-BS
	78	52	10	35	M-BS
	89	63	13	28	SF-SUS
	134	74	16	32~44	SF-SUS
	152	80	16	44~58	SF-SUS